Note: Use this document only if you are facing issues during login to ARC/PAC applications when using the Chrome browser.

1. Open Chrome browser. Paste the below URL and press enter.

chrome://flags/#origin-agent-cluster-default

🕉 ARC Index Local 📒 Other 📃 Reference	📃 Index Page 📙 Phire UPG 🏮 real 📀 FN92PRD ARC PRD	🕁 ARC Environment J	S ARC Index-RHEL8 S Opsge
	Q Search flags		Reset all
	header will cause pages to be assigned to an origin-keyed agent clus agent cluster when disabled. Documents whose agent clusters are or document.domain to relax the same-origin policy. – Mac, Windows, L Android, Fuchsia, Lacros #origin-agent-cluster-default	ster, and to a site-keyed igin-keyed cannot set .inux, ChromeOS,	Default v

2. In the above screenshot, the setting shows a value of 'Default'.

Change it to 'Disabled'. You will be prompted to Relaunch chrome. Click on 'Relaunch'. See below.

\rightarrow C O Chrome chrome://flags/#origin-agent-c	luster-default		🖻 🖈 🗖 🚺
Lionmail Fav 📀 ARC Index Local 🧧 Other 📃 Reference	📙 Index Page 📙 Phire UPG 🚦 real 🚷 FN92PRD ARC PRD 🍲 ARC Environment J 🔇	ARC Index-RHEL8 SOpsgenie - Alerts	Other bookma
	Q Search flags	Reset all	
	header will cause pages to be assigned to an origin-keyed agent cluster, and to a site-keyed agent cluster when disabled. Documents whose agent clusters are origin-keyed cannot set document.domain to relax the same-origin policy. – Mac, Windows, Linux, ChromeOS, Android, Fuchis, Lacros <u>Borigin-agent-cluster-default</u>	Disabled V	
	Origin-keyed Processes by default Enables origin-keyed process isolation for most pages (i.e., those assigned to an origin- keyed agent cluster by default). This improves security but also increases the number of processes created. Note: enabling this feature also enables 'Origin-keyed Agent Clusters by default'Mac, Windows, Linux, ChomeOS, Android, Fuchsia, Lacros <u>#origin-keyed-processes-by-default</u>	Default v	
	Code-based RBD Enables the Code-based RBD. – Mac, Windows, Linux, ChromeOS, Fuchsia, Lacros #enable-code-based-tbd	Default ~	
	EditContext API Allows web pages to use the experimental EditContext API to better control text input. – Mac, Windows, Linux, ChromeOS, Android, Fuchsia, Lacros #edit-context	Default v	
	Isolated sandboxed iframes When enabled, applies process isolation to iframes with the 'sandbox' attribute and without the 'allow-same-origin' permission set on that attribute. This also applies to documents with a similar CSP sandboxe header, even in the main frame. The affected sandboxed documents can be grouped into processes based on their URL's site or origin. The default grouping	Default v	×
Your changes will take effect the next time you relaunch	Chrome.		Relaunch

× Experiments × 🧿 New Tab	× + ~ - • ×
	🖻 ★ 🗖 🔃
ronment J 📀 ARC Index-RHEL8 Opsgenie - Alerts	New tab Ctrl+T New window Ctrl+N New Incognito window Ctrl+Shift+N
	History Downloads Ctrl+J Bookmarks Google Password Manager Extensions
3	Zoom - 100% + C1 Print Ctrl+P
Save page as Ctrl+S	Cast Eind More tools
Create shortcut Name window	Edit Cut Copy Paste Settings
Clear browsing data Ctrl+Shift+Del	Help •
Task manager Shift+Esc	Managed by your organization
Developer tools Ctrl+Shift+I	

3. Clear browser cache (as shown below). Then, close and reopen the browser. Login to ARC.

Clea	r browsing data Basic Advanced
Time	range All time
	Browsing history Clears history from all synced devices
	Cookies and other site data Signs you out of most sites. You'll stay signed in to your Google Account so your synced data can be cleared.
	Cached images and files Frees up 109 MB. Some sites may load more slowly on your next visit.
G	<u>Search history</u> and <u>other forms of activity</u> may be saved in your Google Account when you're signed in. You can delete them anytime.
	Cancel Clear data